

A26 Series

410A



Applied COMFORT

INDUSTRY STANDARD SLEEVE

16 x 26"

ROOM AIR CONDITIONERS

COOLING
ONLY

COOLING
+ ELECTRIC HEAT

Applied Comfort™ A26 Series Built-in Air Conditioners.

Direct fit replacement for many models, so all you have to do is take out the old unit and slip in the Applied Comfort Built-In Air Conditioner. It installs in most major sleeves without additional cost of adapter kits or wall remodelling.

High energy efficiency with models up to 9.8 EER saving you energy costs compared to the units you are replacing.

Installs weathertight in most common 16 x 26" sleeves with the use of trim kit.

Premium Components provide exceptional reliability, durability, low sound, and long-life.

Warranty by Applied Comfort Products Inc.

Applied Comfort has been designing and manufacturing premium quality PTACs since 1994. We provide the following warranty on all of our products:

- 1 year comprehensive parts & labor
- 5 year sealed system parts & labor
- 2nd to 5th year parts including shipping



Loaded with Features.

- 26"(W) X 15-5/8"(H) X 16-7/8"(D)
- Four fan speeds: Auto/Lo/Med/Hi
- Electronic touch pad thermostat
- Hand held controller
- Slide-out chassis
- Efficient rotary compressor

- Fan cycle switch
- 4-way adjustable air discharge
- Hidden vent control
- Energy saver mode
- Easy to clean filter

| Model | A26EC09L00 | A26EC12L00 | A26EC09K00 | A26EC12K00 | A26EC09K35 | A26EC12K35 |
|------------------------------------|---------------|---------------|---------------|---------------|-------------------------|-------------------------|
| Function | COOLING | COOLING | COOLING | COOLING | COOLING + ELECTRIC HEAT | COOLING + ELECTRIC HEAT |
| Rated Voltage | 115V | 115V | 230/208V | 230/208V | 230/208V | 230/208V |
| Rated Frequency | 60Hz | 60Hz | 60Hz | 60Hz | 60Hz | 60Hz |
| Maximum Overcurrent Protection (A) | 15 | 15 | 15 | 15 | 20 | 20 |
| Cooling Capacity (Btu/h) | 9200 | 11800 | 9200/8900 | 11800/11400 | 9200/8900 | 11800/11400 |
| Heating Capacity (Btu/h) | | | | | 11000/9000 | 11000/9000 |
| Power Input Cooling (W) | 940 | 1260 | 940/910 | 1200/1160 | 940/910 | 1200/1160 |
| Power Input Heating (W) | | | | | 3500/2900 | 3500/2900 |
| EER | 9.8 | 9.4 | 9.8 | 9.4 | 9.8 | 9.4 |
| Fan Motor Speed (rpm) (H/M/L) | 1070/1000/920 | 1070/1000/920 | 1070/1000/920 | 1070/1000/920 | 1070/1000/920 | 1070/1000/920 |
| Dimension (W/H/D) (mm) | 660/397/429 | 660/397/429 | 660/397/429 | 660/397/429 | 660/397/429 | 660/397/429 |
| Dimension of Package (L/W/H) (mm) | 753/620/460 | 753/620/460 | 753/620/460 | 753/620/460 | 753/620/460 | 753/620/460 |
| Net Weight /Gross Weight (lbs) | 86/101 | 86/101 | 86/101 | 86/101 | 86/101 | 86/101 |
| Refrigerant Charge (kg) | R410a/0.6 | R410a/0.63 | R410a/0.59 | R410a/0.63 | R410a/0.59 | R410a/0.63 |

Accessories.

- 16 x 26" Stamped Grille - durable light-weight aluminum
ACC26SAGRILLE ACC26SAGRILLE-CUSTOM
- 16 x 26" Wall Sleeve - powder-coated galvanized steel
ACC26SLEEVE-FULL
- 16 x 27" Expansion Frame - powder-coated galvanized steel
to fit Fedders 16 x 27" sleeve.
ACC26FRAME27

Distributed By:

Applied Comfort Products Inc.
TRUSTED MANUFACTURER OF HIGH QUALITY PTACS